



Pole System

STABLE POSITIONING OF CAMERA

ahlbergcameras.com/products/accessories/pole-system



The Ahlberg Cameras camera pole system is a rigid pole system for keeping strict alignment when carrying a camera during underwater inspection use. It is featured with a lifting hook and a camera adapter for easy handling.

MORE INFORMATION POLE SYSTEM

APPLICATIONS

- Suitable for:
- -IVVI (In Vessel Visual Inspection)
- -Fuel assembly inspection
- -Control rod inspection
- Rigid system with double security joints for precise alignment

BENEFITS

- Available in stainless steel or aluminum
- Brackets, holders, hooks or other parts can be custom designed by request
- Possibility to connect additional poles and thus vary the length of the system
- The camera adaptor at the end of the pole system is designed to fit to most Ahlberg Cameras models
- When connected the system has no loose parts
- The poles are hollow for water inlet/outlet

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width Stainless	44 mm
Width Aluminum	35 mm
Length Stainless	1m, 2m, 3m (39.4", 78.8", 118"). Other lengths, up to 6m, can be manufactured on request.
Length Aluminum	1m, 2m (39.4", 78.8"). Other lengths, up to 6m, can be manufactured on request.
Weight Stainless	1m = 2.4 kg (5.3lbs) , 2m = 3.9 kg (8.6lbs) and 3m = 5.5kg (12.1 lbs)
Weight Aluminum	1m = 0.9 kg (1.16lbs) , 2m = 1.5 kg (3.5lbs)
Camera Adapter Weight	1.3 kg
Lifting Eye Weight	1.2 kg
Maximum Recommended Lifting Weight	100 kg
Material	Stainless steel EN 1.4301/AISI 304 or aluminum EN 6082

We reserve the right to alter specifications without prior notice

POLE SYSTEM IMAGES



We reserve the right to alter specifications without prior notice